


[2016-Sep.-NewBraindump2go 400-201 PDF Study Guide 414q&as [NQ71-NQ80 Download

2016.09 New 400-201: Cisco CCIE Service Provider Written Exam v4.1 Exam Questions Updated Today! Free Download 400-201 Exam Dumps(PDF & VCE) 414Q&As from Braindump2go.com Today!100% Real Exam Questions! 100% Exam Pass Guaranteed! **NEW QUESTION 71 - NEW QUESTION 80** 1.|2016 New 400-201 Exam Dumps(PDF & VCE) 414Q&As Download:<http://www.braindump2go.com/400-201.html2>.|2016 New 400-201 Exam Questions & Answers:<https://drive.google.com/folderview?id=0B75b5xYLjSSNRjJsZE5Fd04xYTQ&usp=sharing> QUESTION 71In which way does the DS-Lite IPv6 transitioning mechanism differ from IPv6 Dual-Stack? A. DS-Lite is a combination of tunnel and translation technologies.B. DS-Lite is a transition technology that gives full IPv6 connectivity for IPv6 capable hosts that are on the IPv4 Internet but have no native connection to an IPv6 network.C. DS-Lite is an automatic tunnel where the tunnel destination is determined by the IPv4 address extracted from the IPv6 address that starts with the prefix 2002::/16.D. DS-Lite is a stateless tunneling mechanism with a lightweight and secure manner without requiring upgrades to existing IPv4 access network infrastructure. Answer: AExplanation:

http://www.cisco.com/c/en/us/products/collateral/service-provider/carrier-grade-ipv6-solution/white_paper_c11-558744-00.html

QUESTION 72Refer to the exhibit. Customer XYZ Site 1 is not learning prefixes from Site 2. What is the issue?



A. MPLS LSP is broken along the path.B. The route-policy is not implemented in router PE-2.C. The BGP local-as command should be used between PE-1 and CE-1.D. The route-distinguisher values must match in both sites.E. The BGP as-override command should be implemented between between PE-1 and CE-1. Answer: E QUESTION 73Which two models are the models of DiffServ-Aware Traffic Engineering? (Choose two) A. Policy-based ModelB. Class based ModelC. Russian Doll ModelD. Global Tunnel ModelE. Maximum Allocation Model Answer: CE QUESTION 74What is one of the primary overhead fields associated with the Optical Payload Unit (OPU)? A. path monitoringB. tandem connection monitoring activation deactivation (TCM ACT)C. Payload Structure Identifier (PSI)D. multiframe alignment signal (MFAS)E. section monitoring Answer: C QUESTION 75Process-level redundancy is implemented by a system manager process that creates the standby process. What two functions are provided by the system-level process called Qnet Symlink Manager (QSM)? (Choose two.) A. backing up the information for the broken connectionsB. provides common information for connecting processes and servicesC. detection of a failed connectionD. provides an abstract name for a process or serviceE. distribution of symbolic link information Answer: DE QUESTION 76IP over DWDM management models (Choose two.) A. Segmented ManagementB. Integrated ManagementC. Virtual TransponderD. Traffic Management Answer: AB QUESTION 77A Service Provider wants to extend MPLS WAN endpoints in the cloud at the edge of a customer network within the cloud. Which platform will meet this requirement? A. Cisco NX-OSB. Cisco CSR1000vC. Cisco ISR Routers running IOSD. Cisco CRS-1E. Cisco ASR Routers running IOS-XR Answer: BExplanation:

<http://www.cisco.com/c/en/us/products/collateral/routers/cloud-services-router-1000v-series/datasheet-c78-733443.html>

QUESTION 78Which MPLS technology will achieve LAN extensions over the service provider backbone? A. AToMB. VPLS C. L2VPND. L2TPv3 Answer: BExplanation:<https://tools.ietf.org/html/rfc7041> QUESTION 79All secure domain routers (SDRs) have shared attribute and resources. Which three resources are shared all SDRs? (Choose three.) A. privilege-level configurationB. fabric cardsC. SNMP trapsD. admin-level configurationE. exec-level configuration Answer: BCD QUESTION 80Refer to the exhibit. Which three statements describe r RIB-Failure in the show ip bgp command output? (Choose three.)

```
RI> show ip bgp
BGP table version is 5, local router ID is 2.100.200.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               * -> failed
Network        Next Hop        Metric LocPrf Weight Path
*> 6.6.6.0/24   10.10.13.3      0 130 0 30 i
*> 7.7.7.0/24   10.10.13.3      0 125 0 30 i
```

A. It is a redundancy route. B. It is a route with a better administrative distance already present in IGP. C. The number of routes in VRF exceeds the route limit that is configured under the VRF instance. D. It is a rerouting entry. E. It indicates memory failure. Answer: BCE **!!!RECOMMEND!!!** 1. [Braindump2go|2016 New 400-201 PDF & 400-201 VCE 414Q&As Download:](http://www.braindump2go.com/400-201.html)
<http://www.braindump2go.com/400-201.html> 2. [Braindump2go|2016 New 400-201 Questions & Answers:](https://drive.google.com/folderview?id=0B75b5xYLjSSNRjJsZE5Fd04xYTQ&usp=sharing)
<https://drive.google.com/folderview?id=0B75b5xYLjSSNRjJsZE5Fd04xYTQ&usp=sharing>