

[March-2018Braindump2go 300-075 Exam VCE Instant Download][104-114

2018 March Latest Cisco 300-075 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-075 Real Exam Questions:1.[2018 Latest 300-075 Exam Dumps (PDF & VCE) 391Q&As Download:

<https://www.braindump2go.com/300-075.html>2.[2018 Latest 300-075 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNOXRpM1hydUpDU3M?usp=sharing>QUESTION 104When you connect a Cisco VCS Control to Cisco Unified Communications Manager by using a SIP trunk, which mechanism do you use to verify that the trunk has an active connection?A. OPTIONS pingB. DNS tracingC. Continuous pingD. Dynamic DNSAnswer:

AQUESTION 105Which DNS SRV Records must be configured on the external DNS server in a mobile remote access scenario with Cisco Expressway?A. _collab-edge._tls.example.comB. _collab-edge._udp.example.comC. _cisco-uds._tcp.example.comD. _cuplogin._tcp.example.comAnswer: AQUESTION 106Company X currently uses a Cisco Unified Communications Manager, which has been configured for IP desk phones and Jabber soft phones. Users report however that whenever they are out of the office, a VPN must be set up before their Jabber client can be used. The administrator for Company X has deployed a Collaboration Expressway server at the edge of the network in an attempt to remove the need for VPN when doing voice. However, devices outside cannot register.Which two additional steps are needed to complete this deployment? (Choose two.)A. A SIP trunk has to be set up between the Expressway-C and Cisco UCM.B. An additional interface must be enabled on the Cisco UCM and placed in the same subnet at the Expressway.C. The customer firewall must be configured with any rule for the IP address of the external Jabber client.D. The Expressway server needs a neighbor zone created that points to Cisco UCM.E. Jabber cannot connect to Cisco UCM unless it is on the same network or a VPN is set up from outside.Answer: ADQUESTION 107A new administrator at Company X has deployed a VCS Control on the LAN and VCS Expressway in the DMZ to facilitate VPN-less SIP calls with users outside of the network. However, the users report that calls via the VCS are erratic and not very consistent.What must the administrator configure on the firewall to stabilize this deployment?A. The VCS Control should not be on the LAN, but it must be located in the DMZ with the Expressway.B. The firewall at Company X must have all SIP ALG functions disabled.C. The firewall at Company X requires a rule to allow all traffic from the DMZ to pass to the same network that the VCS Control is on.D. A TMS server is needed to allow the firewall traversal to occur between the VCS Expressway and the VCS Control servers.Answer: BQUESTION 108The VCS Expressway can be configured with security controls to safeguard external calls and endpoints. One such option is the control of trusted endpoints via a whitelist.Where is this option enabled?A. on the voice-enabled firewall at the edge of the networkB. on the VCS under Configuration > registration > configurationC. on the TMS server under Registrations > whitelistD. on the VCS under System > configuration > RegistrationsAnswer: BQUESTION 109Which statement about configuring the Cisco VCS Control and Cisco VCS Expressway is true?A. You do not need to configure search rules for traversal calls.B. You need to configure the firewall to allow communication from the Cisco VCS Expressway to the Cisco VCS Control.C. The username on the Cisco VCS Control and Cisco VCS Expressway are local and do not need to match.D. The Cisco VCS Expressway is the Traversal Server.Answer: DQUESTION 110Company X wants to implement RSVP-based Call Admission Control and move away from the current location-based configuration.Where does the administrator go to create a default profile?A. System > Call Manager > Clusterwide > Service Parameters > RSVPB. System > Service Parameters > RSVP.C. System > Service Parameters > Call Manager > Clusterwide parameters > RSVPD. on each MGCP gateway at all remote locationsAnswer: CQUESTION 111Where can you change the clusterwide DSCP setting for Cisco Unified Communications Manager?A. enterprise parametersB. service parametersC. enterprise phone configurationD. Ethernet configurationAnswer: BQUESTION 112Refer to the exhibit. What is the correct value to use for the "DSCP for TelePresence Calls" Cisco CallManager service parameter? A. 28 (011100)B. 34 (100010)C. 41 (101001)D. 46 (101110)Answer: BQUESTION 113Which two statements about remote survivability are true? (Choose two.)A. SRST supports more Cisco IP Phones than Cisco Unified Communications Manager Express in SRST mode.B. Cisco Unified Communications Manager Express in SRST mode supports more Cisco IP Phones than SRST.C. MGCP fallback is required for ISDN call preservation.D. MGCP fallback functions with SRST.Answer: ADQUESTION 114Which two options enable routers to provide basic call handling support for Cisco Unified IP Phones if they lose connection to all Cisco Unified Communications Manager systems? (Choose two.)A. SCCP fallbackB. Cisco Unified Survivable Remote Site TelephonyC. Cisco Unified Communications Manager ExpressD. MGCP fallbackE. Cisco Unified Communications Manager Express in SRST modeAnswer: BE!!!RECOMMEND!!!1.[2018 Latest 300-075 Exam Dumps (PDF & VCE) 391Q&As Download:<https://www.braindump2go.com/300-075.html>2.[2018 Latest 300-075 Study Guide Video: YouTube Video: [YouTube.com/watch?v=SEoPn-rPUT4](https://www.youtube.com/watch?v=SEoPn-rPUT4)