

[May-2018-NewExam Pass 100% !Braindump2go 300-206 VCE and 300-206 PDF Dumps 315Q Instant Download[119-129]

2018 May New Cisco 300-206 Exam Dumps with PDF and VCE Just Updated Today! Following are some new 300-206 Real

Exam Questions: 1.|2018 Latest 300-206 Exam Dumps (PDF & VCE) 315Q Download:

<https://www.braindump2go.com/300-206.html>2.|2018 Latest 300-206 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNOXZTcmdGNEh2UU0?usp=sharing>QUESTION 119Which two

configurations are necessary to enable password-less SSH login to an IOS router? (Choose two.)A. Enter a copy of the administrator's public key within the SSH key-chainB. Enter a copy of the administrator's private key within the SSH key-chainC.

Generate a 512-bit RSA key to enable SSH on the routerD. Generate an RSA key of at least 768 bits to enable SSH on the router

E. Generate a 512-bit ECDSA key to enable SSH on the routerF. Generate a ECDSA key of at least 768 bits to enable SSH on

the router**Answer: AD**QUESTION 120Which two features does Cisco Security Manager provide? (Choose two.)A. Configuration and policy deployment before device discoveryB. Health and performance monitoringC. Event management and alertingD.

Command line menu for troubleshootingE. Ticketing management and tracking**Answer: BC**QUESTION 121An administrator

installed a Cisco ASA that runs version 9.1. You are asked to configure the firewall through Cisco ASDM.When you attempt to

connect to a Cisco ASA with a default configuration, which username and password grants you full access?A. admin / adminB.

asaAdmin / (no password)C. It is not possible to use Cisco ASDM until a username and password are created via the username

usernamepassword password CLI command.D. enable_15 / (no password)E. cisco / cisco**Answer: D**QUESTION 122Which

three options are default settings for NTP parameters on a Cisco ASA? (Choose three.)A. NTP authentication is enabled.B. NTP

authentication is disabled.C. NTP logging is enabled.D. NTP logging is disabled.E. NTP traffic is not restricted.F. NTP

traffic is restricted.**Answer: BDE**QUESTION 123Which two options are purposes of the packet-tracer command? (Choose two.)A.

to filter and monitor ingress traffic to a switchB. to configure an interface-specific packet traceC. to simulate network traffic

through a data pathD. to debug packet drops in a production networkE. to automatically correct an ACL entry in an ASA

Answer: CDQUESTION 124Refer to the exhibit. Server A is a busy server that offers these services:- World Wide Web- DNS

Which command captures http traffic from Host A to Server A? A. capture traffic match udp host 10.1.1.150 host 10.2.2.100B.

capture traffic match 80 host 10.1.1.150 host 10.2.2.100C. capture traffic match ip 10.2.2.0 255.255.255.192 host 10.1.1.150D.

capture traffic match tcp host 10.1.1.150 host 10.2.2.100E. capture traffic match tcp host 10.2.2.100 host 10.1.1.150 eq 80**Answer:**

DQUESTION 125Your company is replacing a high-availability pair of Cisco ASA 5550 firewalls with the newer Cisco ASA

5555-X models. Due to budget constraints, one Cisco ASA 5550 will be replaced at a time.Which statement about the minimum

requirements to set up stateful failover between these two firewalls is true?A. You must install the USB failover cable between the

two Cisco ASAs and provide a 1 Gigabit Ethernet interface for state exchange.B. It is not possible to use failover between different

Cisco ASA models.C. You must have at least 1 Gigabit Ethernet interface between the two Cisco ASAs for state exchange.D.

You must use two dedicated interfaces. One link is dedicated to state exchange and the other link is for heartbeats.**Answer: B**

QUESTION 126In which two modes is zone-based firewall high availability available? (Choose two.)A. IPv4 onlyB. IPv6 only

C. IPv4 and IPv6D. routed mode onlyE. transparent mode onlyF. both transparent and routed modes**Answer: CD**

QUESTION 127You are the administrator of a multicontext transparent-mode Cisco ASA that uses a shared interface that belongs to

more than one context. Because the same interface will be used within all three contexts, which statement describes how you will

ensure that return traffic will reach the correct context?A. Interfaces may not be shared between contexts in routed mode.B.

Configure a unique MAC address per context with the no mac-address auto command.C. Configure a unique MAC address per

context with the mac-address auto command.D. Use static routes on the Cisco ASA to ensure that traffic reaches the correct

context.**Answer: C**QUESTION 128A rogue device has connected to the network and has become the STP root bridge, which has

caused a network availability issue.Which two commands can protect against this problem? (Choose two.)A.

switch(config)#spanning-tree portfast bpduguard defaultB. switch(config)#spanning-tree portfast bpdufilter defaultC.

switch(config-if)#spanning-tree portfastD. switch(config-if)#spanning-tree portfast disableE. switch(config-if)#switchport

port-security violation protectF. switch(config-if)#spanning-tree port-priority 0**Answer: AC**QUESTION 129According to Cisco

best practices, which two interface configuration commands help prevent VLAN hopping attacks? (Choose two.)A. switchport

mode accessB. switchport access vlan 2C. switchport mode trunkD. switchport access vlan 1E. switchport trunk native vlan 1

F. switchport protected**Answer: AB**!!!REDDOMMEND!!!1.|2018 Latest 300-206 Exam Dumps (PDF & VCE) 315Q Download:

<https://www.braindump2go.com/300-206.html>2.|2018 Latest 300-206 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=WvexFqQgoA](https://www.youtube.com/watch?v=WvexFqQgoA)