New Released Cisco 300-206 Real Exam Questions Provided By Braindump2go For Free Download (81-90)

Cisco Official News: Important News: Cisco 300-206 Exam Questions are been updated recently! The Cisco 300-206 Practice Exam is a very hard exam to successfully pass your exam. Here you will find Free Braindump2go Cisco Practice Sample Exam Test Questions that will help you prepare in passing the 300-206 exam. Braindump2go Guarantees you 100% PASS exam JN0-360! Vendor: Cisco Exam Code: 300-206 Exam Name: Implementing Cisco Edge Network Security Solutions Keywords: 300-206 Exam Dumps, 300-206 Practice Tests, 300-206 Practice Exams, 300-206 Exam Questions, 300-206 PDF, 300-206 VCE

Free,300-206 Book,300-206 E-Book,300-206 Study Guide,300-206 Braindump,300-206 Prep Guide

Pass4sure	Braindur
	100% Pass OR N
160 Q&As - Practice	184 Q&As – Real Q
\$109.99	\$99.99
No Discount	Coupon Code: BDN

Compared Before Buying Cisco

QUESTION 81 What are two primary purposes of Layer 2 detection in Cisco IPS networks? (Choose two.) A. identifying Layer 2 ARP attacks B. detecting spoofed MAC addresses and tracking 802.1X actions and data communication after a successful client association C. detecting and preventing MAC address spoofing in switched environments D. mitigating man-in-the-middle attacks Answer: AD QUESTION 82 What is the primary purpose of stateful pattern recognition in Cisco IPS networks? A. mitigating man-in-the-middle attacks B. using multipacket inspection across all protocols to identify vulnerability-based attacks and to thwart attacks that hide within a data stream C. detecting and preventing MAC address spoofing in switched environments D. #160; dentifying Layer 2 ARP attacks Answer: B QUESTION 83 What are two reasons to implement Cisco IOS MPLS Bandwidth-Assured Layer 2 Services? (Choose two.) A. guaranteed bandwidth and peak rates as well as low cycle periods, regardless of which systems access the device B. increased resiliency through MPLS FRR for AToM circuits and better bandwidth utilization through MPLS TE C. enabled services over an IP/MPLS infrastructure, for enhanced MPLS Layer 2 functionality D. provided complete proactive protection against frame and device spoofing Answer: BC QUESTION 84 What is the maximum jumbo frame size for IPS standalone appliances with 1G and 10G fixed or add-on interfaces? A. 1024 bytes B. 1518 bytes C. 2156 bytes D. 9216 bytes Answer: D QUESTION 85 Which two statements about Cisco IDS are true? (Choose two.) A. It is preferred for detection-only deployment. B. It is used for installations that require strong network-based protection and that include sensor tuning. C. It is used to boost sensor sensitivity at the expense of false positives. D. It is used to monitor critical systems and to avoid false positives that block traffic. E. It is used primarily to inspect egress traffic, to filter outgoing threats. Answer: BC QUESTION 86 What are two reasons for implementing NIPS at enterprise Internet edges? (Choose two.) A. Internet edges typically have a lower volume of traffic and threats are easier to detect. B. Internet edges typically have a higher volume of traffic and threats are more difficult to detect. C. Internet edges provide connectivity to the Internet and other external networks. D. Internet edges are exposed to a larger array of threats. E. NIPS is more optimally designed for enterprise Internet edges than for internal network configurations. Answer: CD QUESTION 87 Which statement about the Cisco ASA configuration is true? A. All input traffic on the inside interface is denied by the global ACL. B. All input and output traffic on the outside interface is denied by the global ACL. C. ICMP echo-request traffic is permitted from the inside to the outside, and ICMP echo-reply will be permitted from the outside back to inside. D. HTTP inspection is enabled in the global policy. E. Traffic between two hosts connected to the same interface is permitted. Answer: B QUESTION 88 In the default global policy, which traffic is matched for inspections by default? A. match any B. match default-inspection-traffic C. match access-list D. #160; match port E. match class-default Answer: B QUESTION 89 Which set of commands creates a message

list that includes all severity 2 (critical) messages on a Cisco security device? A. logging list critical_messages level 2 console logging critical_messages B. logging list critical_messages level 2 logging console critical_messages C. logging list critical_messages level 2 logging console enable critical_messages D. logging list enable critical_messages level 2 console logging critical_messages Answer: B QUESTION 90 An administrator is deploying port-security to restrict traffic from certain ports to specific MAC addresses. Which two considerations must an administrator take into account when using the switchport port-security mac-address sticky command? (Choose two.) A. The configuration will be updated with MAC addresses from traffic seen ingressing the port. The configuration will automatically be saved to NVRAM if no other changes to the configuration have been made. B. The configuration will be updated with MAC addresses from traffic seen ingressing the port. The configuration will not automatically be saved to NVRAM. C. Only MAC addresses with the 5th most significant bit of the address (the 'sticky' bit) set to 1 will be learned. D. If configured on a trunk port without the 'vlan' keyword, it will apply to all vlans. E. If configured on a trunk port without the 'vlan' keyword, it will apply only to the native vlan. Answer: BE Braindump2go New Published Exam Dumps: Cisco 300-206 Practice

Tests Questions, 184 Latest Questions and Answers from Official Exam Centre Guarantee You a 100% Pass! Free Download

Instantly!

Compared Before Buying Cisco 300-206 PDF & VCE!		
Pass4sure	Braindump2go	Test King
	100% Pass OR Money Back	
160 Q&As - Practice	184 Q&As – Real Questions	160 Q&As - Practice
\$109.99	\$99.99	\$124.99
No Discount	Coupon Code: BDNT2014	No Discount

http://www.braindump2go.com/300-206.html